



Standard Features

- Complete 180° adjustable
- All Stainless Steel Construction
- Hermetically Sealed (ASME B40-3)
- Accurate to 1% Of Scale
- Standard External Reset
- Silicone fillable for vibration
- 360° Case Rotation



HOW TO ORDER



Models Stem	Length	Connection	Temperature Ranges	Options
<p>Std Models</p> <p>LL = Model L (3" dial, reset)</p> <p>MM = Model M (5" dial, reset) (max temp 550°F)</p> <p>JJ = Model J (4" dial, reset)</p>	<p>025 = 2.5"</p> <p>040 = 4"</p> <p>060 = 6"</p> <p>090 = 9"</p> <p>120 = 12"</p> <p>150 = 15"</p> <p>180 = 18"</p> <p>240 = 24"</p> <p>300 = 30"</p> <p>360 = 36"</p> <p>-</p> <p>Intermediate lengths available up to 80"</p> <p>-Specify length in inches + tenths</p>	<p>Std Threaded</p> <p>1 = 1/2" NPT</p> <p>5 = 3/4" NPT</p> <p>U = 1/2" NPT Bushing</p>	<p>Fahrenheit Ranges</p> <p>F23 = -40 TO 160°F</p> <p>F55* = 25 TO 125°F</p> <p>F43 = 0 TO 200°F</p> <p>F47 = 0 TO 250°F</p> <p>F63 = 50 TO 300°F</p> <p>F67 = 50 TO 500°F</p> <p>F81 = 150 TO 750°F</p> <p>F85 = 200 TO 1000°F</p> <p>Celsius Ranges</p> <p>C23 = -40 TO 70°C</p> <p>C55* = 0 TO 50°C</p> <p>C43 = 0 TO 100°C</p> <p>C47 = -20 TO 120°C</p> <p>C59 = 0 TO 150°C</p> <p>C67 = 0 TO 250°C</p> <p>C81 = 0 TO 400°C</p> <p>C85 = 100 TO 500°C</p> <p>Dual F/C Ranges</p> <p>D23 = -40 TO 160°F & -40 TO 70°C</p> <p>D55* = 25 TO 125°F & 0 TO 50°C</p> <p>D43 = 0 TO 200°F & 0 TO 100°C</p> <p>D47 = 0 TO 250°F & -20 TO 120°C</p> <p>D63 = 50 TO 300°F & 10 TO 150°C</p> <p>D67 = 50 TO 500°F & 0 TO 250°C</p> <p>D81 = 150 TO 750°F & 0 TO 400°C</p> <p>D85 = 200 TO 1000°F & 100 TO 500°C</p>	<p>PS = Pointed Stem</p> <p>SF = Silicone Fill</p> <p>SS = 316 SS Stem</p> <p>F3 = 3/8" dia. Stem</p> <p>PC = Acrylic Window</p> <p>PY = Polycarbonate Window</p> <p>TG = Tempered Glass Window</p> <p>MM = Max/Min Pointer</p>